

*** MATERIAL SAFETY DATA SHEET ***

CLEAN-UP SOLVENT #327 J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)

(PAGE 1)

DATE OF PREP: 03/10/97

SECTION I

DISTRIBUTOR : U. V. PROCESS SUPPLY, INC.
ADDRESS : 1229 W. CORTLAND ST.
CHICAGO, IL 60614-4805
TELEPHONE #: (773) 248-0099
EMERGENCY#: (800) 535-5053

PRODUCT CLASS: BLEND
MFG.CODE ID : J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)
TRADE NAME : CLEAN-UP SOLVENT #327

SECTION II-A HAZARDOUS COMPONENTS

NO.	COMPONENT	EPC#	% BY WT.
1	DIPROPYLENE GLYCOL MONOMETHYL ETHER	199	76.75
2	TRIMETHYL BENZENE 1,2,4	1162	7.44
3	AROMATIC PETROLEUM NAPHTHA 100	62	14.65

NONE OF THE COMPONENTS OF THIS PRODUCT ARE RECOGNIZED AS CARCINOGENIC. (N/A = NOT APPLICABLE)

SECTION II-B OCCUPATIONAL EXPOSURE LIMITS

NO.	(OSHA) PEL/TWA	PEL/CEILING
1	100.000ppm	N/E
2	25.000ppm	N/E
3	N/E	N/E

NO.	(OSHA) PEL/STEL	SKIN*
1	150.000ppm	Y
2	N/E	N/E
3	N/E	N/E

NO.	(ACGIH) TLV/TWA	TLV/CEILING
1	100.000ppm	N/E
2	25.000ppm	N/E
3	N/E	N/E

NO.	(ACGIH) TLV/STEL	SKIN*
1	150.000ppm	Y
2	N/E	N/E
3	N/E	N/E

MANUFACTURER EXPOSURE LIMITS FOR COMPONENT 3: 50.000ppm

(SKIN) ABSORPTION MAY CONTRIBUTE TO THE OVERALL EXPOSURE TO THIS MATERIAL. TAKE APPROPRIATE MEASURES TO PREVENT SKIN CONTACT.

(Y = YES N = NO N/E = NOT ESTABLISHED)

*** MATERIAL SAFETY DATA SHEET ***

CLEAN-UP SOLVENT #327 J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)

(PAGE 2)

DATE OF PREP: 03/10/97

SECTION III PHYSICAL DATA

BOILING POINT : 305 (DEGREES F)

evaporation rate: < 1 (ether = 1) % solid : not applicable

VAPOR DENSITY : > 1 (AIR = 1) WEIGHT PER GALLON : 7.83 (THEORETICAL)

(Boiling point represents boiling point of lowest boiling raw material.)

SECTION IV HEALTH INFORMATION

• EYE CONTACT

BASED ON THE PRESENCE OF COMPONENT 1 PRODUCT IS PRESUMED TO BE MODERATELY IRRITATING TO THE EYES.

• SKIN CONTACT -EXPOSURE MAY PRODUCE SKIN IRRITATION.

• INHALATION

EXPOSURE MAY PRODUCE IRRITATION TO THE NOSE, THROAT, RESPIRATORY TRACT, AND OTHER MUCOUS MEMBRANES. BASED ON THE PRESENCE OF COMPONENT 3 EXPOSURE TO HIGH CONCENTRATIONS OF VAPOR MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION.

• INGESTION

BASED ON THE PRESENCE OF COMPONENT 3 PRODUCT IS PRESUMED TO BE SLIGHTLY TOXIC. BASED ON THE PRESENCE OF COMPONENT 3 SMALL AMOUNTS OF THE LIQUID ASPIRATED INTO THE LUNGS DURING INGESTION OR FROM VOMITING MAY RESULT IN SEVERE LUNG DAMAGE.

• SIGNS AND SYMPTOMS

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS. SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION. SYMPTOMS OF GASTROINTESTINAL IRRITATION INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA. BASED ON THE PRESENCE OF COMPONENT 3 CENTRAL NERVOUS SYSTEM DEPRESSION MAY BE EVIDENCED BY HEADACHE, DIZZINESS, NAUSEA AND SYMPTOMS OF INTOXICATION; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. SYMPTOMS OF CHRONIC OVEREXPOSURE INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

• AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

• OTHER HEALTH EFFECTS -NONE RECOGNIZED.

SECTION V EMERGENCY AND FIRST AID PROCEDURES

• EYE CONTACT

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF ANY SYMPTOMS PERSIST.

• SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

*** MATERIAL SAFETY DATA SHEET ***

CLEAN-UP SOLVENT #327 J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)

(PAGE 3)

DATE OF PREP: 03/10/97

- **INHALATION**

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

- **INGESTION**

BASED ON THE PRESENCE OF COMPONENT 3, PRODUCT IS PRESUMED TO BE SLIGHTLY TOXIC. BASED ON THE PRESENCE OF COMPONENT 3, SMALL AMOUNTS OF THE LIQUID ASPIRATED INTO THE LUNGS DURING INGESTION OR FROM VOMITING MAY RESULT IN SEVERE LUNG DAMAGE.

- **SIGNS AND SYMPTOMS**

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS. SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH, AND REDUCED LUNG INFECTION. SYMPTOMS OF GASTROINTESTINAL IRRITATION INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA. BASED ON THE PRESENCE OF COMPONENT 3 CENTRAL NERVOUS SYSTEM DEPRESSION MAY BE EVIDENCED BY HEADACHE, DIZZINESS, NAUSEA AND SYMPTOMS OF INTOXICATION; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. SYMPTOMS OF CHRONIC OVEREXPOSURE INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

- **AGGRAVATED MEDICAL CONDITIONS**

PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

- **OTHER HEALTH EFFECTS**

NONE RECOGNIZED.

SECTION VI

EMERGENCY AND FIRST AID PROCEDURES

- **EYE CONTACT**

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF ANY SYMPTOMS PERSIST.

- **SKIN CONTACT**

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

- **INHALATION**

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

- **INGESTION**

DO NOT INDUCE VOMITING. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. SINCE ASPIRATION INTO THE LUNGS CAN CAUSE VERY SERIOUS, PERMANENT DAMAGE, THE DECISION OF WHETHER TO INDUCE VOMITING OR NOT SHOULD BE MADE BY A PHYSICIAN. DANGER FROM LUNG ASPIRATION MUST BE WEIGHED AGAINST TOXICITY WHEN CONSIDERING EMPTYING THE STOMACH. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

*** MATERIAL SAFETY DATA SHEET ***

CLEAN-UP SOLVENT #327 J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)

(PAGE 4)

DATE OF PREP: 03/10/97

- NOTES FOR PHYSICIAN

THE FOLLOWING COMPONENT-SPECIFIC INFORMATION MAY CONTAIN CONTRADICTIONS, AND IS INTENTIONALLY INCLUDED TO GIVE THE ATTENDING PHYSICIAN SPECIFIC INFORMATION ABOUT THE INDIVIDUAL COMPONENTS OF THE BLEND.

>> COMPONENTS 1 AND 3 MAY CAUSE SEVERE, PERMANENT DAMAGE IF ASPIRATED AND VOMITING SHOULD NOT BE INDUCED.

SECTION VI FIRE AND EXPLOSION HAZARDS

FLASH POINT : 108 DEGREES F. TCC

- EXTINGUISHING MEDIA

USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

- SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

WARNING. COMBUSTIBLE. CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT HELMET, FACE SHIELD, BUNKER COAT, GLOVES, RUBBER BOOTS, AND A POSITIVE PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

- UNUSUAL FIRE AND EXPLOSION HAZARDS

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILD UP, WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINERS THAT ARE EXPOSED TO DIRECT FLAME SHOULD BE COOLED WITH WATER TO ELIMINATE STRUCTURAL WEAKENING OF THE CONTAINER'S WALL AND POSSIBLE RUPTURE.

SECTION VII REACTIVITY

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR

- CONDITIONS AND MATERIALS TO AVOID

BASED ON THE PRESENCE OF COMPONENT 1 AVOID OXIDIZING MATERIALS.

- HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION VIII EMPLOYEE PROTECTION

- RESPIRATORY PROTECTION

USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS - AT LEAST 10 AIR CHANGES PER HOUR ARE RECOMMENDED FOR GOOD GENERAL ROOM VENTILATION. IF EXPOSURE EXCEEDS THE PEL/TLV, USE THE APPROPRIATE NIOSH-APPROVED RESPIRATOR.

*** MATERIAL SAFETY DATA SHEET ***

CLEAN-UP SOLVENT #327 J011-014 (1 gal.), J011-015 (5 gal.), J011-016 (55 gal.)

(PAGE 5)

DATE OF PREP: 03/10/97

- PROTECTIVE CLOTHING

WEAR SAFETY GLASSES, GOGGLES, OR A SPLASH SHIELD TO PREVENT EYE CONTACT. CONTACT LENSES SHOULD NOT BE WORN. WEAR APPROPRIATE GLOVES AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND CLOTHING.

- ADDITIONAL PROTECTIVE MEASURES

EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION IX

ENVIRONMENTAL PROTECTION

- SPILL OR LEAK PROCEDURES

LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

- WASTE DISPOSAL

OBSERVE ALL FEDERAL, STATE, AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL.

SECTION X

ADDITIONAL PRECAUTIONS

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS, AND FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER POSSIBLE SOURCES OF IGNITION PRIOR TO USE AND UNTIL VAPORS ARE GONE. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. VAPORS MAY ACCUMULATE AND TRAVEL TO IGNITION SOURCES DISTANT FROM HANDLING SITE. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. CONTAINERS, EVEN IF EMPTY, CAN CONTAIN EXPLOSIVE VAPORS OR RESIDUES. DO NOT CUT, DRILL, GRIND, OR WELD NEAR CONTAINERS

AFTER CONTACT WITH PRODUCT OR CONTAINER WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

UNDER THE PROVISIONS OF TITLE III, SECTION 313 OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR, PART 372, THE FOLLOWING COMPONENTS MAY BE SUBJECT TO REPORTING:

TRIMETHYL BENZENE 1,2,4 (CAS# 000095-63-6)

7.44 WT%

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.