
Hand Pumps for UV inks & coatings

Our complete line of ink and coating pumps includes a full assortment of diaphragm, double-diaphragm, peristaltic, hand, drum and 5-gallon pumps for every need



FIVE GALLON CONTAINER HAND PUMP (1)

Hand operated pump for 5 gallon containers. A complete unit, once assembled, it directly replaces the original cover on a 5 gal pail. Ink or coating can be pumped directly to the application equipment or into smaller containers.

Item No. Description

J004-001 FIVE GALLON CONTAINER HAND PUMP



The affordable CON-TROL-CURE™ Polyethylene Hand Pump provides high resistance to most UV inks and coatings, inert and strong acids, alkalies and many solvents for contamination-free and long-term use. Its positive down stroke pressure provides smooth transferring of materials to 12 feet (3.6 m). Empties 55 gallon drums to within 1/8" of bottom. Mounted in 2" diameter (51 mm) standard V-threaded polyethylene plug.



Item No. Description


J004-045 POLYETHYLENE HAND PUMP

NICKEL-PLATED HAND PUMP (3)

The self-priming Nickel-Plated Hand Pump fits 15-, 30- and 55-gallon drums with 1-1/2" or 2" openings. Resists chemical reaction to non-corrosive liquids. Pumps 12 ounces per stroke. Measures 41-3/8" high x 1-7/16" diameter.

Item No. Description

J004-028 NICKEL-PLATED HAND PUMP



SOLVENT DRUM HAND PUMP (4)

The hand operated CON-TROL-CURE™ Solvent Drum Pump is constructed of the finest materials and is resistant to most solvents. Self-priming, this unit will easily dispense 12 ounces per stroke. Designed for heavy use and years of reliable service. For 15, 30 and 55 gallon drums. Measures 41-3/8"H x 1-7/16"D at base. For low viscosity materials.

Item No. Description

J004-027 SOLVENT DRUM HAND PUMP

24-HOUR PRODUCT SERVICES

Internet: www.uvprocess.com E-mail: info@uvps.com



Hand Pumps for UV inks & coatings

Our complete line of ink and coating pumps includes a full assortment of diaphragm, double-diaphragm, peristaltic, hand, drum and 5-gallon pumps for every need




LOW VISCOSITY PLASTIC HAND PUMP (5)

The deluxe CON-TROL-CURE™ Low Viscosity Plastic Pump is constructed of non-corrosive, hi-density polyethylene and stainless steel. Ideal for pumping low viscosity conventional or UV inks and coatings from drum storage containers. Simple lever action handle dispenses 8 ounces per stroke. For 15-, 30- and 55gallon drums with 1-1/2" or 2" opening. Measures 15-1/4" high x 1" diameter.

Item No. **Description**

LOW VISCOSITY PLASTIC HAND PUMP J004-012




PLASTIC CHEMICAL HAND PUMP (6)

Chemical- and acid-resistant hand pump conveniently adjusts to 2, 4, 6 or 8 oz pumping action. Fits 55 gallon drums with 3/4 or 2" opening. 48"H x 9/16" diameter. For low to medium viscosity UV coatings, solvent and fountain solutions, water- and solvent-based coatings.

Item No. Description

J004-026 PLASTIC CHEMICAL HAND PUMP




PLASTIC SIPHON/PUMP - 55 GALLON (7)

Upright polyethylene drum pump resists solvents for transferring petroleumbased products. Bung-mounts onto any 55-gallon drum. Extended hose reduces splashing.

Item No. **Description**

PLASTIC SIPHON/PUMP - 55 GALLON J004-100



24-HOUR PRODUCT SERVICES

Internet: www.uvprocess.com E-mail: info@uvps.com

