
SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FLUORESCENT MARKING PEN C098-003
DISTRIBUTER: UV PROCESS SUPPLY, INC..
ADDRESS: 1229 W. CORTLAND STREET
CHICAGO, IL 60614-4805
EMERGENCY PHONE: 800-688-4005 - VEOLIA
OTHER CALLS: 773-248-0099
FAX PHONE: 773-880-6647
PREPARED ON: MAY 21, 2012

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS NO.</u>	<u>% VOL</u>	<u>SARA 313 Reportable</u>	<u>Exposure Limit ACGIH-TLV</u>	<u>Exposure Limit OSHA PEL</u>
Isopropyl Alcohol	67-63-0	50-60	400	ppm	400 ppm

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: As noted in the preface to published values adopted by the ACGIH, TLV's represent "conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. Because of wide variation in individual susceptibility however, a small percentage of workers may experience discomfort from some substances at concentration at or below the threshold limit; a smaller percentage might be affected more seriously by aggravation of a pre-existing condition or by development of occupational illness"

ROUTES OF ENTRY: Dermal contact. Eye contact. Inhalation. Ingestion.

POTENTIAL ACUTE HEALTH EFFECTS

EYES: Irritation to eyes. May cause redness or temporary swelling. Vapors also may irritate eyes.

SKIN: May be irritating to sensitive skin

INGESTION: May cause nausea and or vomiting

INHALATION: Moderately irritating to nasal and respiratory tracts. Can cause headache and nausea

SECTION 4: FIRST AID MEASURES

INGESTION: Give two glasses of lukewarm water. Do not induce vomiting without medical advice. Seek medical attention.

EYES: Flush immediately with water for at least 15 minutes. Seek medical attention.

SKIN: Wash with soap and water.

INHALATION: Remove to fresh air.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT: 56 F

FLAMMABLE LIMITS: LEL: 4.3 VEL: 19.0
LEL value reported is lowest listed for any ingredient in mixture.

EXTINGUISHING MEDIA: Water fog. Multipurpose foam, Dry chemical, CO2

SPECIAL FIREFIGHTING PROCEDURES: Fight as volatile liquid fire. Water in ink will stop fire after initial flash. Water on fire may cause frothing.

AUTOIGNITION TEMPERATURE: 797 F

HMIS HAZARD CLASSIFICATION

HEALTH: 1 FLAMMABILITY: 3 REACTIVITY: 0
PROTECTION: A

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Secure area and remove all sources of ignition and heat. Prevent additional discharge of material. Ventilate area. Flush and dilute with water; wipe up with rags or other absorbent material. Do not allow spills to enter sewers or water courses. Dispose of waste in accordance with applicable government regulations. Dilute with water and boil to evaporation. Wear chemical goggles, gloves, boots and protective clothing. Wear respirator if necessary.

SECTION 7: HANDLING AND STORAGE

HANDLING: Do not ingest. Do not get in eyes. Keep container closed. Use only with adequate ventilation. Do not breathe vapor or mist.

STORAGE: Keep container tightly closed. Keep container in a cool, well ventilated area.

STORAGE TEMPERATURE: 40-90 F

SHELF LIFE: 12 months from date of manufacture

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses must not be worn.

SKIN PROTECTION: Depending on the conditions of use, protective gloves may be worn for cleanliness.

RESPIRATORY PROTECTION: If workplace exposure limits of product or any component is exceeded, NIOSH/MSHA approved respiratory protection must be used.

ENGINEERING CONTROLS: Provide local exhaust or general room ventilation equal to outdoors to minimize exposure to vapors.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Liquid

ODOR: Mild

BOILING POINT (OF): >200

VAPOR PRESSURE (=Hg): 44.0

VAPOR DENSITY (Air= 1): approx. 1.6

SOLUBILITY IN WATER: Complete

SPECIFIC GRAVITY (H₂O=1): 0.79

VOC: 23.71 gms/l

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Heat, sparks and open flame

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Burning may produce CO and CO₂

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID (POLYMERIZATION): None

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Oral Toxicity: Low toxicity: LD₅₀ >2000 mg/kg, Rat

Acute Dermal Toxicity: Low toxicity: LD₅₀ >2000 mg/kg, Rabbit

Acute Inhalation Toxicity: Low toxicity: LC₅₀ >5000 ppm / 1 hours, Rat

High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Skin Irritation: Not irritating to skin.

Eye Irritation: Irritating to eyes

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

Sensitisation: Not a skin sensitizer.

Repeated Dose Toxicity: Kidney: caused kidney effects in male rats which are not considered relevant to humans

SECTION 12: ECOLOGICAL INFORMATION

Fish - Low toxicity: LC/EC/IC50 > 100 mg/l

Aquatic Invertebrates - Low toxicity: LC/EC/IC50 > 1000 mg/l

Algae - Expected to have low toxicity: LC/EC/IC50 > 1000 mg/l

Microrganisms - Low toxicity: LC/EC/IC50 > 1000 mg/l

Mobility - Dissolves in water. If product enters soil, it will be highly mobile and may contaminate groundwater.

Persistence/degradability - Readily biodegradable meeting the 10 day window criterion. Oxidises rapidly by photo-chemical reactions in air.

Bioaccumulation - Not expected to bioaccumulate significantly.

SECTION 13: DISPOSAL CONSIDERATIONS

Consult Federal, State and Local Regulations for accepted procedures of disposal, and any reporting or notification requirements.

SECTION 14: TRANSPORT INFORMATION

Refer to the following when using the below information and reshipping Inks and Thinners:

FLASH POINT 73 – 149 (HAZARDOUS BY GROUND IN 5 GALLON CONTAINER)

FLASHPOINT UNDER 73 (HAZARDOUS BY GROUND IN QUART OR LARGER CONTAINER)

AND FLASHPOINT 149 OR UNDER (HAZARDOUS BY AIR IN ANY UNIT OF MEASURE)

If size deems shipment hazardous, below markings are required

U.S. DEPARTMENT OF TRANSPORTATION (LAND, D.O.T.)

PROPER SHIPPING NAME: Printing Ink

HAZARD CLASS: 3

ID NUMBER: 1210

PACKING GROUP: II

WATER TRANSPORTATION (WATER, I.M.O.)

PROPER SHIPPING NAME: Printing Ink

HAZARD CLASS: 3

ID NUMBER: 1210

PACKING GROUP: II

AIR TRANSPORTATION (AIR, I.C.A.O.)

PROPER SHIPPING NAME: Printing Ink

HAZARD CLASS: 3

ID NUMBER: 1210

PACKING GROUP: II

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): Ingredients listed

Isopropyl Alcohol CAS 67-63-0

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES: immediate (acute) health hazard, delayed (chronic) health hazard, fire hazard

313 REPORTABLE INGREDIENTS: None

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: The hazards listed on this MSDS are taken from the MSDS for each of the ingredients in this mixture. In most cases, the maximum form of hazard is represented here. The TLV's represent the conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. It must be remembered that each individual reacts differently and some may experience discomfort while others do not. This MSDS is presented so that each individual will have the information to deal safely with the use of this product. All material's TSCA listed.

PREPARATION INFORMATION: Prepared by UV Process Supply, Inc.

DATE PREPARED: MAY 21, 2012

This MSDS supercedes all previously dated MSDS for this product.

DISCLAIMER: As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim all liability for any use of this material. Information contained herein is given in good faith and is believed to be true and accurate. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or results to be obtained from the use thereof.